

HIP profiles

MOUNTING

Surface mount / Suspended

COLOUR

White / Black

LAMP

Tridonic stark LLE24 HE

WATTAGE/ LUMEN P/ MTR

HE 350mA: 16.5W p/mtr 1,646lm p/mtr HE 400mA: 19.0W p/mtr 1,880lm p/mtr HE 450mA: 21.2W p/mtr 2,085lm p/mtr HE 500mA: 23.7W p/mtr 2,288lm p/mtr

COLOUR TEMP

3000K / 4000K

DIMMING


Dali / Switched

LENS

Opal V

LIFETIME

L90/B10 45,000 hours @ 400mA L70/B10 123,000 hours @ 400mA















*see next page for products where 5 days manufacturing lead time applies.





We have a large selection of profile light specifications that can be manufactured within 5 working days.

	LENGTH	MOUNTING	COLOUR	CURRENT	COLOUR TEMPERATUR	E DIMMING
(e.g. <u>HIP</u> <u>1025</u> <u>S</u> <u>B</u> <u>40</u> <u>3</u> <u>S</u>)						
HIP	<u>1025</u> mm	<u>S</u> urface Mount	<u>B</u> lack	40 0mA	<u>3</u> 000K	<u>S</u> witched
	<u>1235</u> mm	<u>SU</u> spended	<u>W</u> hite	<u>50</u> 0mA	<u>4</u> 000K	<u>D</u> ali
	<u>1585</u> mm					
	<u>1795</u> mm					
	2145 mm					
	<u>2565</u> mm					

^{*}For dimming options, Switched will always be 400mA and Dali will always be 500mA.

If your requirements are outside of these specifications, contact us to discuss lead times.





