

2021 PRODUCT CATALOGUE




NOVA10

POWER ANYWHERE



NOWAD

NOMAD, a division of Vynco Industries (NZ) Limited, has specialised in durable, reliable and customised portable power solutions since 1994. NOMAD is part of Vynco's mission to bring innovative NZ designed, developed, and manufactured electrical products to the New Zealand market. 100% owned by the Vale family, Vynco today employs over 100 employees nationwide - with offices across Auckland, Christchurch and Wellington.



Focusing on research and development, Vynco's 15-strong Product Development team creates and develops products that challenge traditional ideas. Based in Christchurch, the Product Development team work with the brightest talent from New Zealand universities to develop local skill and provide opportunities to future engineers. Our in-house Quality & Compliance team ensures our products are checked and tested to a high standard and our product is supported throughout its lifetime.



Vynco's NZ-based manufacturing facilities offer a variety of customisation options. Utilising in-house manufacturing and local suppliers allows Vynco to accommodate changes in local regulations with efficiency and ease and gives us the ability to adapt and customise to meet the ever-evolving needs of the industry, the electrician and end-user. With three plants, we are proudly part of the manufacturing community, keeping jobs within NZ.




Sustainability is a key value underpinning Vynco's operation and we strive to reduce the amount of waste created by the New Zealand construction and electrical markets. Through our introduction of moulded fibre product packaging, digitalisation, operational changes, local manufacturing and constant design improvements, Vynco is leading the industry in creating a more environmentally-friendly future.



Research & Development

All products throughout this book have been researched & developed by Vynco's in-house Product Development team.



**4 Way IP44
Powerboard**
designed for the
New Zealand Army.

NOMAD4 OUTLET POWER BOARD

CODE	OUTLETS	QUANTITY	VOLTAGE	CONFIGURATION
NOMAD4	10A	4	230V	Auto Socket AS/NZ 2P +E

PROTECTION

IP56

INPUT

RCBO (MCB/RCD) = 10A 30mA, 1P+N TypeA 6kA 230V

- Two piece polycarbonate housing with rubber seal
- Complies with AS/NZS3012 & AS/NZS3190
- Can be hung from a wall fixing



NOMAD6 OUTLET POWER BOARD

CODE	OUTLETS	QUANTITY	VOLTAGE	CONFIGURATION
NOMAD6	10A	6	230V	Auto Socket AS/NZ 2P +E

PROTECTION

IP56

INPUT

RCBO (MCB/RCD) = 10A 30mA, 1P+N TypeA 6kA 230V

- Roto-molded polyethylene housing
- Complies with AS/NZS3012 & AS/NZS3190
- 2x USB Outlets (5V 2.1Amp)
- Phone holder
- Carry handle
- Handle also acts as a hanging bracket
- 15 & 16 Amp versions available on request



32A POWER SUPPLY UNIT

CODE	INPUT	WEIGHT	PROTECTION
N32	1 X 32A, 400V, 3PH + E + N, IEC	16KG	IP65
OUTLETS	QUANTITY	VOLTAGE	CONFIGURATION
32A*	1	400V	IEC, 3PH + E + N
16A	1	230V	IEC, 2P + E (RCD PROTECTED)
15A AUTOSOCKET	10	230V	AS/NZ, 2P + E (RCD PROTECTED)

Complies with AS/NZS3190:2011 & AS/NZS3012:2010

63A POWER SUPPLY UNIT

CODE	INPUT	WEIGHT	PROTECTION
N63	1 X 63A, 400V, 3PH + E + N	17KG	IP65
OUTLETS	QUANTITY	VOLTAGE	CONFIGURATION
63A*	1	400V	IEC, 3PH + E + N
32A*	1	400V	IEC, 3PH + E + N
32A	1	400V	AS/NZ, 3P + E + N (RCD PROTECTED)
16A	1	230V	IEC, 2P + E (RCD PROTECTED)
10A AUTOSOCKET	4	230V	AS/NZ, 2P + E (RCD PROTECTED)

Complies with AS/NZS3190:2011 & AS/NZS3012:2010

*Interconnection Outlets



NOMAD K2 STAND

CODE

DESCRIPTION

NOMADK2

Powder Coated Steel K2 Stand without gear trays

NOMADK2A

Powder Coated Steel K2 Stand
complete with 2x Aluminium Gear Trays

FOR USE WITH

CODE

DESCRIPTION

NOMADK2HB

Hangover Bar to keep cables elevated

N63

N63 Power Supply Unit

N32

N32 Power Supply Unit

NOMAD6

NOMAD6 Power Board

Customisation

Customisation options available.



NOMADK2A with A) N32 Power Supply Unit,
B) Hangover Bar, and C) NOMAD6 Power Board mounted.

MAIN DISTRIBUTION

CODE	INPUT
NOMAD250	250A, 400V, 3PH + E + N

Features

- IK10
- IP65 cabinet
- IP66 external sockets
- Weather-resistant
- Aluminium base tray for storage (not shown)
- Fork liftable
- Mobile robust frame
- Crane hooks available on request

Customisation

Customised units available from 250A to 800A with any configuration of outlets. Metering options also available.

Specifications

- 250A MCCB
- 3x 63A IEC 5 Pin Sockets (MCB Protected)
- 3x 32A IEC 5 Pin Sockets (MCB Protected)
- 4x 15A 3 Flat Pin Sockets (RCD/MCB Protected)
- 2x 16A IEC 3 Pin Sockets (RCD/MCB Protected)



INTERCONNECTING LEADS				
CODE	LENGTH	AMPERAGE	VOLTAGE	CABLE
NL1010	10M	10A	250V	2.5mm ² , 3 Core
NL1020	20M	10A	250V	2.5mm ² , 3 Core
NL3210	10M	32A	400V	6mm ² 3PH + E + N
NL3220	20M	32A	400V	6mm ² 3PH + E + N
NL3230	30M	32A	400V	6mm ² 3PH + E + N
NL3240	40M	32A	400V	6mm ² 3PH + E + N
NL6310	10M	63A	400V	16mm ² 3PH + E + N
NL6320	20M	63A	400V	16mm ² 3PH + E + N
NL6330	30M	63A	400V	16mm ² 3PH + E + N
NL6340	40M	63A	400V	16mm ² 3PH + E + N

32A and 63A NOMAD interconnecting leads are supplied with Mennekes IEC 60309 plugs and connectors and heavy duty XLPE insulated cable. The 32A and 63A cable is screened.




NL1010




NL3220

SITE POWER LAYOUT EXAMPLES

SITE 1



SITE 2



SABRE 2 SITE LIGHTING

CODE	POWER	CONNECTION	LAMP	LUMEN OUTPUT	LIGHTS	PROTECTION
NOMADL10C2A	230-240V A.C 0.1A	10A, IP66 3 Flat Pin Plug and Connector	Single Fitting 9W / Chain of 2x 18W	1300lm per Light	2	IP65 / IK08

Eliminate the need for several bulky lights with the SABRE 2 temporary site lighting.

- 5m total cord length, 2.5m length between light modules.
- Durable construction - IK08.
- Polycarbonate housing and lens.
- Rubberised cord block and hanging clip.
- Can be daisy chained for larger areas max of 50x light chains (100x lights).
- Easily stored in tool bag or hung in work vehicle.
- Complies with AS/NZS60598.1 & AS/NZS60598.2.20
- For interior and exterior use.



NOMADL10C2A



SABRE 10 SITE LIGHTING

CODE	POWER	CONNECTION	LAMP	LUMEN OUTPUT	LIGHTS	PROTECTION
NOMADL10	230-240V A.C 0.5A	16A, IP67 3 Round Pin Plug and Connector	Single Fitting 9W / Chain of 10x 90W	1300lm per Light	10	IP65 / IK08
NOMADL10A	230-240V A.C 0.5A	10A, IP66 3 Flat Pin Plug and Connector	Single Fitting 9W / Chain of 10x 90W	1300lm per Light	10	IP65 / IK08

- 25m total cord length, 2.5m length between light modules.
- Durable construction - IK08.
- Polycarbonate housing and lens.
- Rubberised cord block and hanging clip.
- Can be daisy chained for larger areas max of 10x light chains (100x lights).
- Complies with AS/NZS60598.1 & AS/NZS60598.2.20
- For interior and exterior use.



PORTABLE LED LIGHT FITTINGS

CODE	PLUG/SOCKET	FITTING SIZE	WEIGHT
NOMADL4M	IEC 16A, IP65, 16A, 3 Pin*	4ft	4.5 kg
SUPPLY	LED LAMP	SUPPLY LEAD	
230V-240V, 50Hz	2ft 35W/4ft 45W	1.5mm ² . 5m	

*Other configurations available on request



PORTABLE LED LIGHT FITTINGS WITH BATTERY BACKUP

CODE	PLUG/SOCKET	INTERNAL BATTERY BACKUP	WEIGHT
NOMADL2MBB	IEC, 2P + E 16A	1 hour of light after loss or disconnection of power. Can be used in conjunction with any NOMAD Series LED Light.	3.5 kg
SUPPLY	LED LAMP	SUPPLY LEAD	
230V-240V, 50Hz	2ft 20W	1.5mm ² . 5m	



NOTES

NOTES





NO/MA/ND

POWER ANYWHERE

CHRISTCHURCH

388 - 396 Tuam Street,
Philipstown,
Christchurch 8011

PO Box 9022, Tower Junction,
Christchurch 8149
New Zealand

P +64 3 335 0366

F +64 3 335 0980

E sales@vynco.co.nz

vynco.co.nz

AUCKLAND

9 Levene Place,
Mt. Wellington,
Auckland 1060

PO Box 12 249, Penrose,
Auckland 1642
New Zealand

P +64 9 526 7881

F +64 9 525 5799

E sales@vynco.co.nz